



## Main

Range	ZENcelo
Product or component type	Telephone + data socket
Device application	Communication
Socket additional information	Shuttered
Colour tint	White

## Complementary

Communication network category	Voice: 3 Data: 5e
Insulation resistance	$\geq 200$ MOhm
Number of gangs	2 gangs
Contacts material	Contact: phosphor bronze with gold plating IDC contact: phosphor bronze with nickel plating
Material	Polycarbonate plastic part
Device mounting	Surface Flush
Width	87 Mm
Height	87 Mm
Depth	36 Mm
Embedding depth	30.2 Mm

## Environment

AWG gauge	AWG 34...AWG 23 (4 twisted pair cables)
Dielectric strength	1000 V for 60 s at 60 Hz
Ambient air temperature for operation	0...35 °C
Relative humidity	0...95 %
Environmental characteristic	No UV resistant
Standards	ASTMD4566-98 TIA/EIA-568-B.2-1

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	93.0 G
Package 1 Height	3.1 Cm
Package 1 Width	8.6 Cm

Package 1 Length	8.6 Cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	1.027 Kg
Package 2 Height	9.5 Cm
Package 2 Width	19 Cm
Package 2 Length	19.5 Cm
Unit Type of Package 3	CAR
Number of Units in Package 3	60
Package 3 Weight	6.642 Kg
Package 3 Height	21.5 Cm
Package 3 Width	30 Cm
Package 3 Length	40 Cm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

Product Life Status : **Commercialised**