



Main

Range of product	ZENcelo
Product or component type	Message indicator
Cover frame colour tint	White

Complementary

Device mounting	Surface Flush
Clamping connection capacity	3 x 2.5 mm ² for solid cable(s) 3 x 2.5 mm ² for stranded cable(s) 4 x 1.5 mm ² for solid cable(s) 4 x 1.5 mm ² for stranded cable(s)
[Ue] rated operational voltage	250 V AC 50/60 Hz
Local signalling	Do not disturb: indicator light, neon (orange) Please clean up: indicator light, neon (green)
Material	Brass: contact Polycarbonate: base Polycarbonate: cover Polycarbonate: grid plate Polycarbonate: surround
Connections - terminals	Illuminated indicators: folded terminal
Operating altitude	<= 2000 m
Embedding depth	19.57 Mm
Width	87 Mm
Height	87 Mm
Depth	27.72 Mm

Environment

Maximum ambient air temperature for operation	35 °C
Relative humidity	0...95 %
Environmental characteristic	No UV resistant
Standards	MS IEC 60669-1 EN 60669-1 IEC 60669-1 GB 16915.1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.27 Cm
Package 1 Width	8.6 Cm
Package 1 Length	8.6 Cm
Package 1 Weight	99.0 G
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	9.5 Cm
Package 2 Width	19.0 Cm
Package 2 Length	19.5 Cm
Package 2 Weight	1.087 Kg
Unit Type of Package 3	CAR
Number of Units in Package 3	60
Package 3 Height	21.5 Cm
Package 3 Width	30.0 Cm
Package 3 Length	40.0 Cm
Package 3 Weight	7.002 Kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Product Life Status : **Commercialised**