



Main

Range	ZENcelo
Product or component type	Switch
Number of gangs	1 gang

Complementary

Device mounting	Surface Flush
Rated current	16 AX at 250 V AC 50/60 Hz
Local signalling	Please clean up: indicator light, neon (green) Do not disturb: indicator light, neon (amber)
Material	Grid plate: polycarbonate + GF 20 % Base: polycarbonate Cover: polycarbonate Surround: polycarbonate
Load type	Incandescent lamp Fluorescent lamp Inductive
Cover frame colour tint	Silver bronze
Connections - terminals	Brass rod terminals
Width	43.9 Mm
Height	50.7 Mm
Depth	1.8 Mm






Environment

Ambient air temperature for operation	-5...35 °C
Relative humidity	0...95 %
Environmental characteristic	No UV resistant
Operating altitude	2000 m
Standards	GB 16915.1 MS IEC 60669-1 SS 227-1 IEC 60669-1 BS EN 60669-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	73.0 G
Package 1 Height	3.7 Cm
Package 1 Width	8.8 Cm
Package 1 Length	8.9 Cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	825.0 G
Package 2 Height	9.5 Cm
Package 2 Width	19 Cm
Package 2 Length	19.5 Cm
Unit Type of Package 3	CAR
Number of Units in Package 3	60
Package 3 Weight	5.43 Kg
Package 3 Height	21.5 Cm
Package 3 Width	30 Cm
Package 3 Length	40 Cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile

Product Life Status : **Commercialised**