



Main

Range	ZENcelo
Product or component type	Switch
Device application	Bell switch
Load type	Resistive Inductive lamp
Colour tint	White
Cover frame colour tint	White

Complementary

Device mounting	Flush Surface
Rated current	10 A at 250 V AC 50/60 Hz
Local signalling	Please clean up: indicator light, neon (green) Do not disturb: indicator light, neon (orange)
Number of gangs	2 gangs
Material	Brass: contact Polycarbonate: base Polycarbonate: cover Polycarbonate: grid plate Polycarbonate: surround
Connections - terminals	Pillar terminals
Width	87 Mm
Height	87 Mm
Depth	27.72 Mm

Environment

Ambient air temperature for operation	-5...35 °C
Relative humidity	0...95 %
Environmental characteristic	No UV resistant
Operating altitude	2000 m
Standards	IEC 60669-1 GB 16915.1 MS IEC 60669-1 BS EN 60669-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3 Cm
Package 1 Width	8.72 Cm
Package 1 Length	8.72 Cm
Package 1 Weight	113.8 G
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	15 Cm
Package 2 Width	19 Cm
Package 2 Length	8 Cm
Package 2 Weight	1.11 Kg
Unit Type of Package 3	CAR
Number of Units in Package 3	80
Package 3 Height	21 Cm
Package 3 Width	32.5 Cm
Package 3 Length	50 Cm
Package 3 Weight	11604 G

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**