



Main

Range	ZENcelo
Product or component type	Switch
Device application	Bell switch
Number of gangs	1 gang

Complementary

Device mounting	Flush Surface
Rated current	10 A at 250 V AC 50/60 Hz
Local signalling	Do not disturb: indicator light, neon (orange)
Material	Base: polycarbonate Cover: polycarbonate Surround: polycarbonate Contact: brass Grid plate: polycarbonate
Load type	Inductive lamp Resistive
Cover frame colour tint	Silver bronze
Connections - terminals	Pillar terminals
Width	87 Mm
Height	87 Mm
Depth	27.72 Mm

Environment

Ambient air temperature for operation	-5...35 °C
Relative humidity	0...95 %
Environmental characteristic	No UV resistant
Operating altitude	2000 m
Standards	MS IEC 60669-1 GB 16915.1 BS EN 60669-1 IEC 60669-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	88.0 G
Package 1 Height	3.4 Cm
Package 1 Width	8.6 Cm
Package 1 Length	8.6 Cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	972.0 G
Package 2 Height	9.5 Cm
Package 2 Width	19 Cm
Package 2 Length	19.5 Cm
Unit Type of Package 3	CAR
Number of Units in Package 3	60
Package 3 Weight	6.312 Kg
Package 3 Height	21.5 Cm
Package 3 Width	30 Cm
Package 3 Length	40 Cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Product Life Status : **Commercialised**