



## Main

Product or component type	Shaver socket
Installation direction	Vertical
Input voltage	240 V AC 50 Hz
Output voltage	115 V AC 50 Hz 240 V AC 50 Hz
Material	Polycarbonate: base Polycarbonate: grid plate Polycarbonate: surround
Cover frame colour tint	Silver bronze

## Complementary

Device mounting	Surface Flush
Cable cross section	1...2.5 Mm <sup>2</sup>
Rated operational power in VA	20 VA
Connections - terminals	Pillar terminal without pressure plate
Electrical insulation class	Class B
Width	147 Mm
Height	87 Mm
Depth	49.3 Mm

## Environment

Environmental characteristic	No UV resistant
Operating altitude	<= 2000 m
IP degree of protection	IP21
Standards	IEC 61558-1
Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.3 Cm
Package 1 Width	9.4 Cm
Package 1 Length	15.5 Cm
Package 1 Weight	600 G
Unit Type of Package 2	CAR

Number of Units in Package 2	20
Package 2 Height	16.3 Cm
Package 2 Width	33 Cm
Package 2 Length	50.4 Cm
Package 2 Weight	12.54 Kg
Unit Type of Package 3	P06
Number of Units in Package 3	160
Package 3 Height	105 Cm
Package 3 Width	60 Cm
Package 3 Length	80 Cm
Package 3 Weight	105.32 Kg

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>

Product Life Status : **Commercialised**