



Main

Range	ZENcelo
Product or component type	USB charger
Device presentation	Mechanism
Colour tint	White (RAL 9003)
Number of terminals	2 screw terminals

Complementary

Device mounting	Flush
Surface finish	Glossy
Surface treatment	Untreated
Number of modules	1 module 46 x 36.7 x 21.7 mm
Fixing mode	Screw
[Ue] rated operational voltage	100/240 V AC 50/60 Hz
Integrated connection type	1 USB port 5 V DC, maximum load current: 2.1 A
Material	Silicone rubber: cover PC (polycarbonate): grid plate PC (polycarbonate): housing
Shape of screw head	Cross
Clamping connection capacity	2.5 mm ² for stranded cable(s) 2.5 mm ² for flexible cable(s) 2.5 mm ² for rigid cable(s) 1.5 mm ² for stranded cable(s) 1.5 mm ² for flexible cable(s) 1.5 mm ² for rigid cable(s)
Wire stripping length	6 Mm
Product compatibility	Apple Power bank HW Samsung XiaoMi Major smart phone and tablet HTC
Height	87 Mm
Width	87 Mm
Depth	37.1 Mm
Embedding depth	27.3 Mm
Product weight	0.0773 Kg

Environment

Ambient air temperature for storage	-5...60 °C
Relative humidity	10...90 %
Product certifications	CCC IEC
IP degree of protection	IP20
Environmental characteristic	Liquid soap Alcohol

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	83.0 G
Package 1 Height	3.8 Cm
Package 1 Width	8.8 Cm
Package 1 Length	8.8 Cm
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Weight	664.0 G
Package 2 Height	9.5 Cm
Package 2 Width	15 Cm
Package 2 Length	19 Cm
Unit Type of Package 3	CAR
Number of Units in Package 3	80
Package 3 Weight	6680.0 G
Package 3 Height	21 Cm
Package 3 Width	31 Cm
Package 3 Length	50 Cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Product Life Status : **Commercialised**