



## Main

Product or component type	Switch
Load type	DC
Colour tint	Metal gold hairline

## Complementary

Device presentation	Complete product
Rated current	3 A at 24 V DC
Switch application	Panic button
Number of gangs	1 gang
Number of rocker	1
Clamping connection capacity	1 x 1.5 mm <sup>2</sup> for solid cable(s) 1 x 1.5 mm <sup>2</sup> for stranded cable(s)
Connections - terminals	Terminal block
Material	Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: button
Device mounting	Flush Surface
Width	86 Mm
Height	86 Mm
Depth	33.6 Mm

## Environment

IP degree of protection	IP20
Maximum ambient air temperature for operation	45 °C
Operating altitude	2000 m
Relative humidity	0...95 %
Environmental characteristic	UV resistant
Standards	IEC 60670 BS 5733

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.4 Cm
Package 1 Width	8.6 Cm
Package 1 Length	8.6 Cm
Package 1 Weight	63 G
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	9.5 Cm
Package 2 Width	19 Cm
Package 2 Length	19.5 Cm
Package 2 Weight	557 G
Unit Type of Package 3	CAR
Number of Units in Package 3	48
Package 3 Height	21 Cm
Package 3 Width	30 Cm
Package 3 Length	39.5 Cm
Package 3 Weight	3.342 Kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

Product Life Status : **Commercialised**