



Main

Product or component type	Socket-outlet
Device presentation	Complete product
Device application	Power supply
Load type	No inductive load
Colour tint	White
Outlet poles configuration	3P
Outlet standard	British BS 1363A

Complementary

Rated current	13 A at 250 V AC 50 Hz
Socket number	1
Socket-outlet type	Shuttered
Clamping connection capacity	1 x 4...2 x 4 mm ² for solid cable(s) 1 x 4...2 x 4 mm ² for stranded cable(s) 1 x 2.5...3 x 2.5 mm ² for solid cable(s) 1 x 2.5...3 x 2.5 mm ² for stranded cable(s)
Connections - terminals	Folded terminal
Material	Polycarbonate grid plate Polycarbonate surround Polycarbonate cover
Device mounting	Surface
Width	86 Mm
Height	86 Mm
Depth	27.8 Mm

Environment

IP degree of protection	IP20
Maximum ambient air temperature for operation	45 °C
Ambient air temperature for storage	-5...60 °C
Relative humidity	0...95 %
Environmental characteristic	UV resistant
Standards	BS 1363 SS 145 MS 589
Product certifications	SIRIM

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.8 Cm
Package 1 Width	8.6 Cm
Package 1 Length	8.6 Cm
Package 1 Weight	75.0 G
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	9.5 Cm
Package 2 Width	19.0 Cm
Package 2 Length	19.5 Cm
Package 2 Weight	930.0 G
Unit Type of Package 3	CAR
Number of Units in Package 3	60
Package 3 Height	21.0 Cm
Package 3 Width	30.0 Cm
Package 3 Length	39.5 Cm
Package 3 Weight	5582.0 G

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Product Life Status : **Commercialised**