Product data sheet Characteristics

E8315USB_WE_G11

AvatarOn, 2 USB charger + switched socket, 3P, 13A, White





Main

Product or component type	USB charger + switched socket
Fixing mode	By screws

Complementary

Complementary	
Outlet standard	British
Outlet standard description	With earthing contact
Integrated connection type	2 USB type A 5 V DC 2.1 A 1 socket-outlet 250 V AC 13 A 50/60 Hz
Device mounting	Surface
Device presentation	Complete product
Mounting support	Mounting box
Outlet poles configuration	3P with shutter
Colour tint	White
Surface finish	Matt
Surface treatment	Untreated
Type of packing	Flow-pack
Quantity per set	Set of 10
Ambient air temperature for storage	-560 °C
Protection type	Thermal protection Current protection
Dielectric strength	2000 V
Ambient air temperature for operation	040 °C
Service life in cycles	5000 Cycles
Connections - terminals	Screw terminal
Number of terminals	3
Screwdriver shape	Phillips combined
Number of cables	2
Clamping connection capacity	1.54 mm² for rigid cable(s) 1.54 mm² for stranded cable(s) 1.54 mm² for flexible cable(s)
Material	PC (polycarbonate): grid plate PC (polycarbonate): surround
Wire stripping length	12 Mm
Height	86 Mm
Width	86 Mm
Depth	38.2 Mm

Embedding depth	29.3 Mm	
Standards	UL 1310	
	UL 498	
	UL 94	

Environment

IP degree of protection IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.8 Cm
Package 1 Width	8.6 Cm
Package 1 Length	8.6 Cm
Package 1 Weight	109.0 G
Unit Type of Package 2	BB1
Number of Units in Package 2	60
Package 2 Height	21.0 Cm
Package 2 Width	30.0 Cm
Package 2 Length	39.5 Cm
Package 2 Weight	7.58 Kg

Offer Sustainability

Green Premium product
☑REACh Declaration
Yes
Compliant E EU RoHS Declaration
Yes
Yes
₫Yes
☑ China RoHS Declaration
Product Environmental Profile
☑ End Of Life Information

Product Life Status : Commercialised

