

Product data sheet

Specifications



Socket-outlet, AvatarOn, complete product, 3P, British BS 546, folded terminal polar white

E83426_15_WE_G11

Main

Product or component type	Socket-outlet
Device presentation	Complete product
Device application	Power supply
Load type	No inductive load
Colour tint	White
Outlet poles configuration	3P
Outlet standard	British BS 546

Complementary

Rated current	13 A at 250 V AC 50 Hz
Socket number	1
Socket-outlet type	Shuttered
Clamping connection capacity	1 x 4...2 x 4 mm ² for solid cable(s) 1 x 4...2 x 4 mm ² for stranded cable(s) 1 x 2.5...3 x 2.5 mm ² for solid cable(s) 1 x 2.5...3 x 2.5 mm ² for stranded cable(s)
Connections - terminals	Folded terminal
Material	Polycarbonate grid plate Polycarbonate surround
Device mounting	Surface
Width	86 mm
Height	86 mm
Depth	32.6 mm

Environment

IP degree of protection	IP20
Maximum ambient air temperature for operation	45 °C
Ambient air temperature for storage	-5...60 °C
Relative humidity	0...95 %
Environmental characteristic	UV resistant
Standards	SS 472

Product certifications SIRIM

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Package 1 Height 3.3 cm

Package 1 Width 8.6 cm

Package 1 Length 8.6 cm

Package 1 Weight 81.0 g

Unit Type of Package 2 BB1

Number of Units in Package 2 10

Package 2 Height 9.5 cm

Package 2 Width 19.0 cm

Package 2 Length 19.5 cm

Package 2 Weight 982.0 g

Unit Type of Package 3 CAR

Number of Units in Package 3 60

Package 3 Height 21.0 cm

Package 3 Width 30.0 cm

Package 3 Length 39.5 cm

Package 3 Weight 5894.0 g

Offer Sustainability

Sustainable offer status Green Premium product

REACH Regulation [REACH Declaration](#)

REACH free of SVHC Yes

EU RoHS Directive Compliant
[EU RoHS Declaration](#)

Toxic heavy metal free Yes

Mercury free Yes

RoHS exemption information [Yes](#)

China RoHS Regulation [China RoHS declaration](#)
Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure [Product Environmental Profile](#)

Recommended replacement(s)