



### Main

Product or component type	USB charger
Integrated connection type	2 USB type A 5 V DC, maximum load current: 2.1 A

### Complementary

Device mounting	Flush
Device presentation	Complete product
Colour tint	Light wood
Surface finish	Glossy
[Ue] rated operational voltage	100/240 V AC 50/60 Hz
Output current	2.1 A
Material	PC (polycarbonate)
Connections - terminals	Screw terminals
Screwdriver shape	Phillips combined
Clamping connection capacity	1.5...2.5 mm <sup>2</sup> for flexible cable(s) 1.5...2.5 mm <sup>2</sup> for rigid cable(s)
Height	86 Mm
Width	86 Mm
Depth	40 Mm

### Environment

Standards	IEC 60950-1
Electrical insulation class	Class II
IP degree of protection	IP20

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.4 Cm
Package 1 Width	8.6 Cm
Package 1 Length	8.6 Cm
Package 1 Weight	100 G
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	9.5 Cm
Package 2 Width	19 Cm

Package 2 Length	19.5 Cm
Package 2 Weight	880 G
Unit Type of Package 3	CAR
Number of Units in Package 3	48
Package 3 Height	21 Cm
Package 3 Width	30 Cm
Package 3 Length	39.5 Cm
Package 3 Weight	5.28 Kg

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>

Product Life Status : **Commercialised**