

## MQTS2004

- ◆ ✘ Die-cast aluminum radiator
- ◆ ✘ Available in a variety of angles 24°
- ◆ ✘ High lumens and high light efficiency
- ◆ ✘ Rail mounting method
- ◆ ✘ High quality COB LED chips
- ◆ ✘ Comply with LVD, Safe and reliable



Type	Watts	Voltage	PF	Frequency	Luminous Flux 3000K/4000K	Beam Angle	Dimension (mm)	Lifetime (h)	Quantity
MQTS2004/10W	10W	220-240V	0.5	50/60Hz	800/900lm	24°	Ø54,90x145	25000	40/ctn
MQTS2004/20W	20W	220-240V	0.5	50/60Hz	1600/1800lm	24°	Ø62,120x147	25000	30/ctn
MQTS2004/30W	30W	220-240V	0.9	50/60Hz	2400/2700lm	24°	Ø80,130x175	25000	20/ctn

**E S L LIGHTING (M) SDN BHD** (746428-A)

No. 19, 19-1, 19-2, Jalan PDR 6, Kawasan Perniagaan Desa Ria, 43300 Balakong, Seri Kembangan, Selangor.

Tel: 03-8961 2308 Fax: 03-8961 2305

Website: [www.eslighting.com.my](http://www.eslighting.com.my)



Warm White  
3000K



Neutral White  
4000K