

# Product datasheet

Specifications



## 10A 250V 3Gang Momentary switched with Fluorescent Locator, White

E8233PRL1F\_WE\_G11

### Main

Range	Pieno
Product or component type	Switch
Device application	Control
Switch application	Switch
Load type	Resistive Fluorescent
Cover frame colour tint	White

### Complementary

Device mounting	Flush Surface
Wiring device mounting	Flush Surface
Switch function	Momentary
Rated current	10 A at 250 V AC 50 Hz
Local signalling	Fluorescent (white)
Number of gangs	3 gangs
Material	Polycarbonate: surround Polycarbonate: grid plate
Connections - terminals	Pillar terminals
Clamping connection capacity	2 x 1.5 mm <sup>2</sup> for stranded cable(s) 2 x 2.5 mm <sup>2</sup> for solid cable(s)
Embedding depth	23 mm
Width	87 mm
Height	87 mm
Depth	23 mm

### Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	MS IEC 60669-1 IEC 60669-1 GB 16915.1 SS 227-1

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	3.6 cm
<b>Package 1 Width</b>	8.7 cm
<b>Package 1 Length</b>	8.7 cm
<b>Package 1 Weight</b>	105 g
<b>Unit Type of Package 2</b>	BB1
<b>Number of Units in Package 2</b>	6
<b>Package 2 Height</b>	9.5 cm
<b>Package 2 Width</b>	15 cm
<b>Package 2 Length</b>	19 cm
<b>Package 2 Weight</b>	632.238 g
<b>Unit Type of Package 3</b>	CAR
<b>Number of Units in Package 3</b>	60
<b>Package 3 Height</b>	21 cm
<b>Package 3 Width</b>	32.5 cm
<b>Package 3 Length</b>	50 cm
<b>Package 3 Weight</b>	6322.38 g

**Recommended replacement(s)**