

# Product data sheet

Specifications



## 250V 10A 1Gang Bell switched with Illumination DND,PCU,PW

E8231BPDMW\_LS\_G11

**To be discontinued on:** 15 December 2023

**To be discontinued**

### Main

Range	Pieno
Product or component type	Switch
Switch application	Bell switch Control switch
Load type	Fluorescent Resistive
Cover frame colour tint	Lavender silver

### Complementary

Wiring device mounting	Surface Flush
Device mounting	Flush Surface
Switch function	Switch
Rated current	10 A at 250 V AC 50 Hz
Local signalling	Please wait, neon (orange) Please clean up, neon (green) Privacy, neon (red)
Material	Polycarbonate: surround Polycarbonate: grid plate
Connections - terminals	By screw
Clamping connection capacity	1 x 2.5 mm² for solid cable(s) 1 x 1.5 mm² for stranded cable(s)
Embedding depth	21 mm
Width	87 mm
Height	87 mm
Depth	35.5 mm

### Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	GB 16915.1 BS EN 60669-1 IEC 60669-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.6 cm
Package 1 Width	8.7 cm
Package 1 Length	8.7 cm
Package 1 Weight	111 g
Unit Type of Package 2	BB1
Number of Units in Package 2	6
Package 2 Height	9.5 cm
Package 2 Width	15 cm
Package 2 Length	19 cm
Package 2 Weight	667.02 g
Unit Type of Package 3	CAR
Number of Units in Package 3	60
Package 3 Height	21 cm
Package 3 Width	32.5 cm
Package 3 Length	50 cm
Package 3 Weight	6670.2 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

Recommended replacement(s)