

Product datasheet

Specifications



Vivace 16AX 250V 3Gang 2Way Switch, Aluminium silver

KB33_AS_G11

Main

Range	Vivace
Product or component type	Switch
Device short name	KB33
Device application	Control
Switch function	2-way

Complementary

Device presentation	Complete mechanism
Actuator	Rocker
Number of gangs	3 gangs
Colour tint	Aluminium silver
Material	Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: base
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Embedding depth	35 mm
Rated current	16 AX at 250 V AC, inductive 16 AX at 250 V AC, fluorescent
[Ue] rated operational voltage	250 V AC
Network frequency	50 Hz
Contacts material	Brass and phosphor bronze
Connections - terminals	pillar terminal
Terminal identifier	L2 COM L1
Tightening torque	0.4 N.m
Clamping connection capacity	2.5 mm ²
Width	87 mm

Height	87 mm
--------	-------

Environment

Standards	SS 227 MS IEC 60669-1 IEC 60669-1
Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	8.6 cm
Package 1 Length	8.6 cm
Package 1 Weight	113.75 g
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	15.0 cm
Package 2 Width	19.0 cm
Package 2 Length	8.0 cm
Package 2 Weight	910.0 g
Unit Type of Package 3	CAR
Number of Units in Package 3	80
Package 3 Height	22.0 cm
Package 3 Width	32.5 cm
Package 3 Length	50.0 cm
Package 3 Weight	9100.0 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Recommended replacement(s)