

Product datasheet

Specifications



Vivace 16AX 250V 4 Gang 2 Way Switch ,Aluminium silver

KB34_AS_G2

Main

Range	Vivace
Product or component type	Switch
Device short name	KB34
Device application	Control
Device presentation	Complete mechanism

Complementary

Switch function	2-way
Actuator	Rocker
Number of gangs	4 gangs
Colour tint	Aluminium silver
Material	Polycarbonate: grid plate Polycarbonate: surround Nylon: base
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	120.6 mm
Embedding depth	35 mm
Rated current	16 AX at 250 V AC, fluorescent
[Ue] rated operational voltage	250 V AC
Network frequency	50 Hz
Contacts material	Brass and phosphor bronze
Connections - terminals	pillar terminal
Terminal identifier	L1 COM L2
Tightening torque	0.4 N.m
Clamping connection capacity	<= 2.5 mm ²
Width	146 mm

Height	86 mm
---------------	-------

Environment

Standards	SS 227 MS IEC 60669-1 IEC 60669-1
------------------	---

Ambient air temperature for operation	-5...40 °C
--	------------

Relative humidity	0...95 %
--------------------------	----------

Environmental characteristic	Indoor use
-------------------------------------	------------

Recommended replacement(s)