

Product datasheet

Specifications



Vivace 10A 250V 2G Press Switch without marking, White

KB32BP_WE_G11

Main

Range	Vivace
Product or component type	Switch
Device short name	KB32
Device application	Control
Switch function	1-way

Complementary

Device presentation	Complete mechanism
Actuator	Push-button
Number of gangs	2 gangs
Colour tint	White
Material	Polycarbonate: grid plate Polycarbonate: surround Nylon: base
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Embedding depth	35 mm
Rated current	10 A at 250 V AC, inductive
[Ue] rated operational voltage	250 V AC
Network frequency	50 Hz
Contacts material	Brass and phosphor bronze
Connections - terminals	pillar terminal
Terminal identifier	L2 COM
Tightening torque	0.4 N.m
Clamping connection capacity	$\leq 1.5 \text{ mm}^2$
Width	86 mm
Height	86 mm

Environment

Standards	SS 227 MS IEC 60669-1 IEC 60669-1
-----------	---

Ambient air temperature for operation	-5...40 °C
---------------------------------------	------------

Relative humidity	0...95 %
-------------------	----------

Environmental characteristic	Indoor use
------------------------------	------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Weight	71 g
------------------	------

Offer Sustainability

Sustainable offer status	Green Premium product
--------------------------	-----------------------

REACH Regulation	REACH Declaration
------------------	-----------------------------------

EU RoHS Directive	Compliant EU RoHS Declaration
-------------------	--

Mercury free	Yes
--------------	-----

China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
-----------------------	---

RoHS exemption information	Yes
----------------------------	---------------------

Environmental Disclosure	Product Environmental Profile
--------------------------	---

Recommended replacement(s)