

# Product datasheet

Specifications



## Vivace wall plate 1 gang dimmer push button rotary trailing edge 250W 240V

KB31RD250T\_WE\_G11

### Main

Range	Vivace
Range of product	Vivace
Product or component type	Dimmer
Device application	Light control
Device presentation	Complete product
Colour	Black
Quantity per set	Set of 3

### Complementary

Device mounting	Surface
Fixing mode	By 2 screws
Dimmer type	Rotary dimmer
Dimmer application	Capacitive load
Dimmer additional information	2-wire connection
Dimmer control	ON/OFF push, level by turning knob
Control type	Rotary knob
Switch function	1-pole 2-way push-button
Load type	incandescent lamp halogen lamp LED lamp low voltage halogen lamp with electronic transformer, electronic ballast
[Ue] rated operational voltage	230 V AC 50 Hz
Rated current/voltage	10 A at 230 V AC
Protection type	Electronic short-circuit and automatic overload protection
Connections - terminals	Screw terminals
Number of loop terminals	1
Clamping connection capacity	1 x 2.5 mm <sup>2</sup> for solid or flexible with sleeve cable(s) 2 x 1.5 mm <sup>2</sup> for solid or flexible with sleeve cable(s)
Material	Thermoplastic
Surface finish	Glossy
Embedding depth	32 mm

Height	87 mm
Width	87 mm

## Environment

Ambient air temperature for operation	-5...35 °C
Relative humidity	5...95 %
Standards	IEC 60669-1, 1998-Ed.3 + A1, 1999 IEC 60669-2-1, 2002-Ed.4
IP degree of protection	IP20 indoor

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	80 g

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Recommended replacement(s)