

# Product datasheet

Specifications



## Vivace 45A 250V Double Pole Switch with Neon, White

KB31DR45N\_WE

### Main

Range	Vivace
Product or component type	Switch
Device short name	KB31
Device application	Control
Device presentation	Complete mechanism

### Complementary

Switch function	Double 1-way
Actuator	Rocker
Pilot light	Neon indicator lamp
Number of gangs	2 gangs
Colour tint	White
Material	Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: base
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Embedding depth	47 mm
Rated current	45 A at 250 V AC, inductive 45 A at 250 V AC, resistive
[Ue] rated operational voltage	250 V AC
Network frequency	50 Hz
Contacts material	Brass and phosphor bronze
Connections - terminals	pillar terminal
Tightening torque	0.4 N.m
Clamping connection capacity	16 mm <sup>2</sup>
Width	86 mm
Height	86 mm

## Environment

Standards	SS 227 MS IEC 60669-1
Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.6 cm
Package 1 Width	3.7 cm
Package 1 Length	8.6 cm
Package 1 Weight	144.8 g
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	15 cm
Package 2 Width	19.5 cm
Package 2 Length	8 cm
Package 2 Weight	1.159 kg
Unit Type of Package 3	CAR
Number of Units in Package 3	80
Package 3 Height	21 cm
Package 3 Width	31.5 cm
Package 3 Length	50 cm
Package 3 Weight	11836 g

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	<a href="#">Yes</a>

## Recommended replacement(s)