

# Product datasheet

Specifications



## 10AX 250V 3 Gang 2 Way Switch, White

A3G33B2A\_WE\_G11

### Main

|                           |   |
|---------------------------|---|
| Range                     | Affle Plus  |
| Product or component type | Switch  |
| Device application        | Control switch  |
| Load type                 | Incandescent lamp<br>Resistive<br>Inductive<br>Fluorescent lamp |
| Colour tint               | White   |

### Complementary

|                         |   |
|-------------------------|---|
| Device mounting         | Flush   |
| Switch function         | 2-way   |
| Cable cross section     | 4 mm <sup>2</sup> stranded cable<br>2.5 mm <sup>2</sup> solid cable<br>2.5 mm <sup>2</sup> stranded cable<br>9 x 4 mm <sup>2</sup> solid cable for AC |
| Rated current           | 10 AX at 250 V AC   |
| Number of gangs         | 3 gangs   |
| Material                | Polycarbonate: grid plate<br>Polycarbonate: base<br>Polycarbonate: dolly<br>Polycarbonate: surround<br>Polycarbonate: actuator                        |
| Connections - terminals | Screw terminal<br>Brass terminal  |
| Embedding depth         | 24.9 mm   |
| Width                   | 86 mm   |
| Height                  | 86 mm   |
| Depth                   | 35.6 mm   |

### Environment

|   |          |
|---|----------|
| Maximum ambient air temperature for operation | 35 °C    |
| Relative humidity                             | 0...95 % |
| Operating altitude                            | 5000 m   |
| Product certifications                        | IEC      |

|                  |  |
|------------------|--|
| <b>Standards</b> | IEC 60669-1<br>MS IEC 60669-1<br>BS EN 60669-1 |
|------------------|--|

## Packing Units

|                                     |          |
|-------------------------------------|----------|
| <b>Unit Type of Package 1</b>       | PCE      |
| <b>Number of Units in Package 1</b> | 1        |
| <b>Package 1 Height</b>             | 3.6 cm   |
| <b>Package 1 Width</b>              | 8.6 cm   |
| <b>Package 1 Length</b>             | 8.6 cm   |
| <b>Package 1 Weight</b>             | 96 g     |
| <b>Unit Type of Package 2</b>       | BB1      |
| <b>Number of Units in Package 2</b> | 8        |
| <b>Package 2 Height</b>             | 9.5 cm   |
| <b>Package 2 Width</b>              | 15 cm    |
| <b>Package 2 Length</b>             | 19 cm    |
| <b>Package 2 Weight</b>             | 768 g    |
| <b>Unit Type of Package 3</b>       | CAR      |
| <b>Number of Units in Package 3</b> | 96       |
| <b>Package 3 Height</b>             | 21 cm    |
| <b>Package 3 Width</b>              | 39.9 cm  |
| <b>Package 3 Length</b>             | 46.9 cm  |
| <b>Package 3 Weight</b>             | 9.716 kg |

## Offer Sustainability

|                                   |  |
|-----------------------------------|--|
| <b>Sustainable offer status</b>   | Green Premium product                            |
| <b>REACH Regulation</b>           | <a href="#">REACH Declaration</a>                |
| <b>REACH free of SVHC</b>         | Yes  |
| <b>EU RoHS Directive</b>          | Compliant<br><a href="#">EU RoHS Declaration</a> |
| <b>Toxic heavy metal free</b>     | Yes  |
| <b>Mercury free</b>               | Yes  |
| <b>China RoHS Regulation</b>      | <a href="#">China RoHS declaration</a>           |
| <b>RoHS exemption information</b> | <a href="#">Yes</a>                              |
| <b>Environmental Disclosure</b>   | <a href="#">Product Environmental Profile</a>    |

## Recommended replacement(s)