

# Product datasheet

Specifications



## 10AX 250V 1 Gang Intermediate Switch, White

A3G31B3A\_WE\_G11

### Main

Range	Affle Plus
Product or component type	Switch
Device application	Control switch
Load type	Fluorescent lamp Inductive Resistive Incandescent lamp
Colour tint	White

### Complementary

Device mounting	Flush
Switch function	Intermediate
Cable cross section	4 mm <sup>2</sup> stranded cable 2.5 mm <sup>2</sup> solid cable 2.5 mm <sup>2</sup> stranded cable 4 x 4 mm <sup>2</sup> solid cable for AC
Rated current	10 AX at 250 V AC
Number of gangs	1 gang
Material	Polycarbonate: grid plate Polycarbonate: base Polycarbonate: dolly Polycarbonate: surround Polycarbonate: actuator
Connections - terminals	Screw terminal
Embedding depth	24.9 mm
Width	86 mm
Height	86 mm
Depth	35.6 mm

### Environment

Maximum ambient air temperature for operation	35 °C
Relative humidity	0...95 %
Operating altitude	5000 m
Product certifications	IEC
Standards	BS EN 60669-1

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.8 cm
Package 1 Width	8.6 cm
Package 1 Length	8.6 cm
Package 1 Weight	83 g
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	9.5 cm
Package 2 Width	15 cm
Package 2 Length	19 cm
Package 2 Weight	670 g
Unit Type of Package 3	CAR
Number of Units in Package 3	96
Package 3 Height	21 cm
Package 3 Width	39.9 cm
Package 3 Length	46.9 cm
Package 3 Weight	8.54 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Recommended replacement(s)