

Product datasheet

Specifications



Affle plus - 32A 250V 1 gang 1 way double pole switch - white

A3G31D32N_WE_G11

Main

Range	Affle Plus
Product or component type	Switch
Device application	Control switch
Load type	Inductive Resistive
Colour tint	White

Complementary

Device mounting	Flush
Switch function	2-pole 1-way
Cable cross section	6 x 4 mm ² stranded cable for AC 4 x 6 mm ² stranded cable 1 x 10 mm ² stranded cable 1 x 16 mm ² stranded cable
Rated current	32 A at 250 V AC 50 Hz
Local signalling	On: neon, neon lamp (amber)
Number of gangs	1 gang
Material	Polycarbonate: grid plate Polycarbonate: base Polycarbonate: dolly Polycarbonate: surround Brass: terminals Brass: terminal screw
Connections - terminals	Pillar terminal
Embedding depth	22.3 mm
Width	86 mm
Height	86 mm
Depth	35.6 mm

Environment

Maximum ambient air temperature for operation	45 °C
Ambient air temperature for storage	-5...60 °C
Relative humidity	0...95 %

Operating altitude	<= 2000 m
Product certifications	IEC CCC SIRIM
Standards	IEC 60669-1 BS EN 60669-1 MS IEC 60669-1
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	8.6 cm
Package 1 Length	8.6 cm
Package 1 Weight	132 g
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	9.5 cm
Package 2 Width	15 cm
Package 2 Length	19 cm
Package 2 Weight	1.109 kg
Unit Type of Package 3	CAR
Number of Units in Package 3	96
Package 3 Height	21 cm
Package 3 Width	39.9 cm
Package 3 Length	46.9 cm
Package 3 Weight	13.81 kg
SCC14	23606481450586

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Recommended replacement(s)