

Product datasheet

Specifications



Vivace 16A 250V Twin gang Schuko Socket with Shutter, White

KBT426_16S_WE

Main

Product or component type	Socket-outlet
Device short name	KB426
Device application	Power supply
Device presentation	Complete mechanism
Outlet standard deviation	Schuko
Colour tint	White

Complementary

Outlet poles configuration	2 x 2P + E with shutters
Number of gangs	2 gangs
Material	Polycarbonate: grid plate Polycarbonate: surround Nylon: base
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Embedding depth	35 mm
Rated current	16 A at 250 V AC, resistive 16 A at 250 V AC, inductive
Network frequency	50 Hz
Contacts material	Brass and phosphor bronze
Connections - terminals	Pillar terminal
Terminal identifier	N L E
Tightening torque	0.4 N.m
Clamping connection capacity	2.5 mm ²
Width	146 mm
Height	86 mm

Environment

Standards	BS 1363-2
Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use

Packing Units

Unit Type of Package 1	Db
Number of Units in Package 1	1
Package 1 Height	3.9 cm
Package 1 Width	8.6 cm
Package 1 Length	8.6 cm
Package 1 Weight	162.87 g
Unit Type of Package 2	Gyári csomagolás
Number of Units in Package 2	5
Package 2 Height	15 cm
Package 2 Width	19 cm
Package 2 Length	5 cm
Package 2 Weight	884 g
Unit Type of Package 3	CAR
Number of Units in Package 3	50
Package 3 Height	21 cm
Package 3 Width	31.5 cm
Package 3 Length	50 cm
Package 3 Weight	8394 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Recommended replacement(s)