

# Product datasheet

Specifications



## Hotel Key Card

KB31EKT

### Main

Device short name	KB31
Product or component type	Keycard switch
Device presentation	Complete mechanism

### Complementary

Number of gangs	1 gang
Colour tint	White
Material	Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: base
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Embedding depth	35 mm
Rated current	16 A at 220...240 V AC, resistive load
Network frequency	50/60 Hz
Connections - terminals	Pillar terminal
Terminal identifier	L N
Tightening torque	0.4 N.m
Width	86 mm
Height	86 mm

### Environment

Standards	IEC 60669-2-1
Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	0...60 °C
Relative humidity	0...95 %

---

Environmental characteristic	Indoor use
------------------------------	------------

## Packing Units

---

Unit Type of Package 1	Db
------------------------	----

---

Number of Units in Package 1	1
------------------------------	---

---

Package 1 Weight	169.47 g
------------------	----------

## Offer Sustainability

---

Sustainable offer status	Green Premium product
--------------------------	-----------------------

---

REACH Regulation	<a href="#">REACH Declaration</a>
------------------	-----------------------------------

---

REACH free of SVHC	Yes
--------------------	-----

---

EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
-------------------	--

---

Toxic heavy metal free	Yes
------------------------	-----

---

Mercury free	Yes
--------------	-----

---

China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
-----------------------	---

---

RoHS exemption information	<a href="#">Yes</a>
----------------------------	---------------------

---

Environmental Disclosure	<a href="#">Product Environmental Profile</a>
--------------------------	---

---

Circularity Profile	<a href="#">End of Life Information</a>
---------------------	---

## Contractual warranty

---

Warranty	18 months
----------	-----------

Recommended replacement(s)