

Product datasheet

Specifications



ESM 13A 250V surface mount switched socket

ESM15_G11

Main

Range	S-Classic
Product or component type	Switched socket
Device application	Power supply
Outlet poles configuration	2P + E with shutter
Rated current	13 A at 250 V AC 50/60 Hz

Complementary

Device presentation	Complete product
Number of gangs	1 gang
Device mounting	Surface
Material	Plate: PC (polycarbonate), white Dolly: PC (polycarbonate), white Base: PP (polypropylene), black
Height	87 mm
Width	87 mm
Depth	47 mm

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	SS 145 MS 589 BS 1363

Packing Units

Unit Type of Package 1	Db
Number of Units in Package 1	1
Package 1 Height	4.2 cm
Package 1 Width	7.8 cm
Package 1 Length	7.8 cm
Package 1 Weight	220.0 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Recommended replacement(s)