

# Product datasheet

Specifications



## ESM 13A 250V Twin gang surface mount switched socket

ESM25\_G11

### Main

Range	S-Classic
Product or component type	Switched socket
Device application	Power supply
Outlet poles configuration	2 x 2P + E with shutters
Rated current	13 A at 250 V AC 50/60 Hz

### Complementary

Device presentation	Complete product
Number of gangs	2 gangs
Device mounting	Surface
Material	Plate: PC (polycarbonate), white Dolly: PC (polycarbonate), white Base: PP (polypropylene), black

### Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	SS 145 MS 589 BS 1363

### Packing Units

Unit Type of Package 1	Db
Number of Units in Package 1	1
Package 1 Height	9.1 cm
Package 1 Width	4.5 cm
Package 1 Length	14.3 cm
Package 1 Weight	435.0 g

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>

<b>EU RoHS Directive</b>	Compliant <a href="#">EU RoHS Declaration</a>
<b>Mercury free</b>	Yes
<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
<b>RoHS exemption information</b>	Yes
<b>Environmental Disclosure</b>	<a href="#">Product Environmental Profile</a>

**Recommended replacement(s)**