

# Product datasheet

Specifications



## ARGUS - Single-Load 180° Dual Technology Occupancy Sensor

SAE\_UE\_MS\_CU1WE

### Main

Range	ARGUS
Product or component type	Occupancy sensor
Device application	Lighting
Load type	Halogen lamp <= 1000 VA Energy saving lamp <= 80 VA Incandescent lamp <= 2000 W Low voltage halogen lamp <= 1000 VA Fluorescent lamp 100 µF <= 900 VA HVAC <= 5 A 30 V DC HVAC <= 10 A 250 V AC cos phi = 1

### Complementary

Rated voltage	230 V +/- 10 % AC 50/60 Hz
Detection angle	180°
Presence detection area	PIR: 360°, 8 m US: 180°, 10 x 16 m
Device mounting	Flush Surface
Mounting support	Ceiling
Mounting height	2...3 m
Diameter	111.5 mm
Depth	72 mm surface mounted 90 mm flush mounting

### Environment

Electrical shock protection class	Class II
IP degree of protection	IP20
Ambient air temperature for operation	0...45 °C
Standards	EN 55015 EN 61000-3-3 EN 60669-1 EN 60669-2-1 EN 61000-3-2 EN 61547 EN 55022

## Packing Units

Unit Type of Package 1	Db
Number of Units in Package 1	1
Package 1 Height	12.1 cm
Package 1 Width	9.1 cm
Package 1 Length	12.6 cm
Package 1 Weight	280 g
Unit Type of Package 2	CAR
Number of Units in Package 2	20
Package 2 Height	32 cm
Package 2 Width	42 cm
Package 2 Length	51 cm
Package 2 Weight	10200 g

## Offer Sustainability

EU RoHS Directive	Under investigation
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Recommended replacement(s)