

Product data sheet

Specifications



ARGUS - Surface Mount Dual-Load 360° PIR Occupancy Sensor

SAE-UE-MS-CDAWE

Main

Range	ARGUS
Product or component type	Occupancy sensor
Device application	Lighting
Load type	Halogen lamp ≤ 1000 VA Energy saving lamp ≤ 80 VA Incandescent lamp ≤ 2000 W Low voltage halogen lamp ≤ 1000 VA Fluorescent lamp $100 \mu\text{F} \leq 900$ VA HVAC ≤ 5 A 30 V DC HVAC ≤ 5 A 250 V AC $\cos \phi = 1$ HVAC ≤ 1 A 250 V AC $\cos \phi = 0.4$

Complementary

Rated voltage	230 V +/- 10 % AC 50/60 Hz
Detection angle	360°
Presence detection area	PIR: 360°, 7 m
Device mounting	Surface
Mounting support	Ceiling
Mounting height	2...3 m
Diameter	121.5 mm
Depth	42.5 mm

Environment

Electrical shock protection class	Class II
IP degree of protection	IP40
Ambient air temperature for operation	0...45 °C
Standards	EN 60669-1 EN 60669-2-1

Packing Units

Unit Type of Package 1	Db
Number of Units in Package 1	1
Package 1 Height	12.8 cm

Package 1 Width	6.2 cm
Package 1 Length	12.8 cm
Package 1 Weight	280 g
Unit Type of Package 2	CAR
Number of Units in Package 2	48
Package 2 Height	32 cm
Package 2 Width	42 cm
Package 2 Length	51 cm
Package 2 Weight	13.44 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Recommended replacement(s)