

Product datasheet

Specifications



Surface/DIN Mount 24 H Time Switch With Reserve

CCT15101

Main

Product or component type	Mechanical time switch
Number of channels	1
Function available	Manual time changeover

Complementary

Device application	Building
Load type	LED lamp 200 VA Compact fluorescent lamp 200 VA
Cycle duration	24 h
Minimum interval duration	15 min
Type of setting	Manual time changeover
Power consumption in VA	1.5 VA
Maximum switching current	16 A - 230 V AC pf = 1 4 A - 230 V AC pf = 0.6
[Ue] rated operational voltage	230...240 V AC at 50/60 Hz
Backup time	24 h
Mounting support	DIN rail Surface mount
9 mm pitches	4
Colour tint	Grey
Connections - terminals	Screw terminals: 1...2.5 mm ²
Width	72 mm
Height	72 mm
Depth	51 mm

Environment

Ambient air temperature for operation	-20...45 °C
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	Db
------------------------	----

Number of Units in Package 1	1
Package 1 Height	6.5 cm
Package 1 Width	8.05 cm
Package 1 Length	8.05 cm
Package 1 Weight	180 g
Unit Type of Package 2	Doboz
Number of Units in Package 2	48
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	9400 g
Unit Type of Package 3	P12
Number of Units in Package 3	1152
Package 3 Height	105 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	235 kg

Recommended replacement(s)