



Switch Socket - 16A 500V - 3 phase 4 pole - round pin - IP66 (grey)

S56C416GY

Main

Range	WPS
Product or component type	Switch and socket-outlet
Colour tint	Light grey
Motor M-rating AS3133	M120

Complementary

Control type	Rotary
Material	PVC (polyvinyl chloride) UV stabilised
Surface finish	Gloss
Width	101 mm
Height	203 mm
Rated current	16 A
[Ue] rated operational voltage	500 V
Network frequency	50 Hz
Network number of phases	3 phases
Number of gangs	2 gangs
Pin number	4
Device composition	Round pin
Number of poles	3
Mounting mode	Surface mounted

Environment

IP degree of protection IP66

Packing Units

Unit Type of Package 1	Db
Number of Units in Package 1	1
Package 1 Height	11.5 cm
Package 1 Width	10.4 cm
Package 1 Length	20.8 cm

Package 1 Weight	833.333 g
Unit Type of Package 2	CAR
Number of Units in Package 2	12
Package 2 Height	22.1 cm
Package 2 Width	36 cm
Package 2 Length	44.5 cm
Package 2 Weight	10000 g
Unit Type of Package 3	P12
Number of Units in Package 3	240
Package 3 Height	130 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	218000 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Recommended replacement(s)