



HELÓ 150W



HELÓ 200W

LUMINAIRE SPECIFICATIONS

- Power 150W
200W
- Fitting Material Non-Corrosive Die-Cast Aluminium
- Fitting Color Black
- Optical Cover Transparency Tempered Glass
- Ingress Protection IP65
- Impact Protection IK08
- Voltage 220 ~ 240 Vac 50 / 60Hz
- Electrical Safety Class Class I
- Light Efficiency >100 lm/W
- Power Factor >0.9
- Operating Temperature -30 ~ +45°C
- Installation Hook Mounting
- Surge Protections Yes, 4kV
- Pre-Wire 300 mm

APPLICATION

- Warehouses, Multipurpose Halls, Exhibition Halls, Production Areas & Factories

MEASUREMENT & ORDER CODE

WATTAGE	ORDER CODE	TYPICAL LUMINOUS FLUX	TYPICAL WATTAGE	CARTON DIMENSION (L x W x H) mm	NETT WEIGHT
150W	K14112 HELÓ 150W	15000	150	330 x 135 x 330	3.2 kg
200W	K14113 HELÓ 200W	20000	200	390 x 135 x 390	4.2 kg

LED MODULE SPECIFICATIONS

- Color Temperature 5700K Daylight
- Color Rendering Index (CRI) >70
- L70 100,000 Hrs @ 25°C
- PCB Material Metal Core

FEATURES

- Built-In IC Technology
- Direct AC supply Connection (220 ~ 240 Vac 50 / 60Hz)
- No External Driver Required
- High System Efficiency
- Mid Power LEDs
- Thin & Lightweight Size
- Internal Surge Protection Devices (SPD)

COMPLIANCE STANDARD



- LED LM80
- Luminaire EN60598-1, EN60598-2-1, EN55015, EN61547, EN61000







DIMENSION

HELÓ 150W




HELÓ 200W




PHOTOMETRIC

HELÓ 150W



cd/klm
C0/C180: — C90/C270: —

HELÓ 200W



cd/klm
C0/C180: — C90/C270: —

NIKKON®

DRACO HELÓ HIGHBAY



HELÓ 50W



HELÓ 100W

LUMINAIRE SPECIFICATIONS

• Power	50W 100W
• Fitting Material	Non-Corrosive Die-Cast Aluminium
• Fitting Color	Black
• Optical Cover	Transparency Tempered Glass
• Ingress Protection	IP65
• Impact Protection	IK08
• Voltage	220 ~ 240 Vac 50 / 60Hz
• Electrical Safety Class	Class I
• Light Efficiency	>100 lm/W
• Power Factor	>0.9
• Operating Temperature	-30 ~ +45°C
• Installation	Hook Mounting
• Surge Protections	Yes, 4kV
• Pre-Wire	300 mm

APPLICATION

- Eateries, Retails, Hallways, Storage Rooms, Halls & Factories

LED MODULE SPECIFICATIONS

• Color Temperature	5700K Daylight
• Color Rendering Index (CRI)	>70
• L70	100,000 Hrs @ 25°C
• PCB Material	Metal Core

FEATURES

- Built-In IC Technology
- Direct AC Supply Connection (220 ~ 240 Vac 50 / 60Hz)
- No External Driver Required
- High System Efficiency
- Mid Power LEDs
- Thin & Lightweight Size
- Safety Wire
- Internal Surge Protection Devices (SPD)

COMPLIANCE STANDARD

• LED	LM80
• Luminaire	EN60598-1, EN60598-2-1, EN55015, EN61547, EN61000




MEASUREMENT & ORDER CODE

WATTAGE	ORDER CODE	TYPICAL LUMINOUS FLUX	TYPICAL WATTAGE	CARTON DIMENSION (L x W x H) mm	NETT WEIGHT
50W	K14110 HELÓ 50W	5000	50	205 x 94 x 205	1.0 kg
100W	K14111 HELÓ 100W	10000	100	265 x 103 x 265	1.9 kg




DIMENSION

HELÓ 50W




HELÓ 100W



PHOTOMETRIC

HELÓ 50W



HELÓ 100W

