



Motion Sensor  
(Upon Request)

### LUMINAIRE SPECIFICATIONS

• Power	100W 150W 200W 240W 300W
• Fitting Material	Non-Corrosive Die-Cast Aluminium
• Fitting Color	Black
• Optical Cover	PC Cover
• Ingress Protection	IP65
• Voltage	220 ~ 240Vac 50 / 60 Hz
• Electrical Safety Class	Class I
• Operating Temperature	-30 ~ +45°C
• Installation	Hook Mounting
• Pre-Wire	1500mm
• Beam Angle	90D (240W, 300W) 120D (100W, 150W, 200W)

### OPTIONAL FEATURES (UPON REQUEST)

• Sensor	- Motion (Plug & Play) (Except for 300W) - Mounting Height up to 15m with 12m Range Radius - Control with a Remote Control
----------	--

### LED MODULE SPECIFICATIONS

• Color Temperature	5700K Daylight
• Color Rendering Index (CRI)	>70
• L70	100,000 Hrs @ 25°C

### COMPLIANCE STANDARD

• LED	LM80
• Driver	CE, EN/IEC 61347, EN55015, EN61547, EN61000, EN62493, EN62384, UL

### APPLICATION

- Eateries, Retailers, Hallways, Storage Rooms & Halls

### SCENE MODE (REMOTE CONTROL)

SCENE MODE	HOLD TIME	DAYLIGHT TRESHOLD	STAND BY PERIOD	STAND BY DIMMING LEVEL
SC1	30s	2Lux	1min	10%
SC2	5min	10Lux	10min	10%
SC3	10min	50Lux	30min	10%
SC4	30min	Disable	+∞	10%

### MEASUREMENT & ORDER CODE

WATTAGE	ORDER CODE	TYPICAL LUMINOUS FLUX	TYPICAL WATTAGE	CARTON DIMENSION (L x W x H) mm	NETT WEIGHT
100W	UF3 100W	14340	100	428 x 428 x 250	3.9 kg
150W	UF3 150W	20845	150	428 x 428 x 250	3.9 kg
200W	UF3 200W	28356	200	428 x 428 x 250	4.3 kg
240W	UF3 240W	35947	240	428 x 428 x 250	4.3 kg
300W	UF3 300W	44566	300	428 x 428 x 250	5.1 kg




\* Please indicate beam angle when ordering.  
\* All result tested base on 5700K CCT LEDs.



### DIMENSION


100W / 150W  
200W / 240W

300W




### PHOTOMETRIC

90D



cd/klm  
C0/C180: — C90/C270: —

120D



cd/klm  
C0/C180: — C90/C270: —

Note: All specifications are subject to change without prior notice for product improvement. Images, pictures and illustrations used are for illustrative purposes only and the color printed may differ from the actual product.