



Product Code	Description
K245L-D	45A 250V 1 Gang 1 Way Double Pole Switch With Neon



K245L-D



Product back view

Technical Specification

- Rated Voltage: 250VAC, 50/60Hz
- Rated Current: 45A
- Recommended wire size:
 - 10mm² 16mm²
- Isolating Gap Contact: 3mm nominal
- Contact Material: Sliver-Nickel Alloy
- Operating Temperature:
 - -5°C to +40°C
- IP Rating: IP2X

- Dimensions: 86 x 86 x 5mm (WxHxD)
- Fix Center: 60.3 mm
- Fix Screw: M3.5 x 0.6 x 23.5mm±
- Mounting box: >35mm depth
 - R1150, flush mounting, plastic (80 x 80 x 48.4mm) (WxHxD)
 - M1247, flush mounting, metal (79 x 73 x 47mm) (WxHxD)
- Comply to standards:

BSEN 60669


IEC 60669

MS IEC60669





Typical Wiring



(IN - Supply Voltage)

Note:

For high current load application, use the ferrules/sheaths provided for wire terminations.



Product Code	Colour	
K245L-D	White	
K245L-SBL-D	Matt Black (SBL)	
K245L-MSB-D	Matt Silver Black (MSB)	
For other colours, please contact T&J Sales representative		