

LED Highbay UFO DOB - 100W/150W/200W

(Replaces 250W/320W/400W Metal Halide)






AC Input: 220 ~ 240Vac
Colour Temperature: 6000K (available 3000K, 4000K)
Colour Rendering Index (CRI): >70
Beam Angle: 60°
Operating Temperature: -20°C ~ +45°C
Storage Temperature: -20°C ~ +80°C
Lifetime (typical): 50,000 hours at ta 25°C
LED Lumen Maintenance: LM80
Electrical Safety: Class I
LED Driver Compliant: Meet IEC, CE
Heatsink material: Aluminium
Luminaire Cover Material: Frosted PC Lens
IP Rating: IP65



Application areas

- Warehouses
- Multipurpose halls
- Covered walkways
- Retail outlets

| Details | Model | HB-UFO-100W-C60-060-D | HB-UFO-150W-C60-060-D | HB-UFO-200W-C60-060-D |
|---------------------------------|-------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| System Power | | 100W +/-5W | 150W +/-5W | 200W +/-20W |
| Luminaire Efficacy Rating (LER) | | >99 lm/W | >105 lm/W | >105 lm/W |
| Luminous Flux (Initial Lumens) | | 9,460 lm | 15,460 lm | 20,520 lm |
| Weight | | 1.5kg | 2.0kg | 2.0kg |
| Size (ø) x (H) | | 325mm x 80mm | 360mm x 90mm | 360mm x 90mm |
| Photometry | |  |  |  |

