

# LED Greentube - T8

Greentube provides high quality light comparable to conventional fluorescent and delivers the immediate benefits of LED lighting technology. With its simple design, it is easy to install in any location.

**AC Input:** 200 ~ 240Vac  
**System Power:** 18W +/-5%  
**Color Rendering Index (CRI):** >80  
**Beam Angle:** 180°  
**Operating Temperature:** -20°C ~ +40°C  
**Storage Temperature:** -20°C ~ +80°C  
**Lifetime (typical):** 40,000 hours at ta 25°C  
**Usage:** 12 hours a day  
**LED Lumen Maintenance:** LM80  
**Electrical Safety:** Class II  
**Compliant:** CE  
**Weight:** 250g  
**Luminaire Material:** Frosted Polycarbonate  
**Size(L) X (Ø) :** 1198mm x 26mm



#### Application areas

- Homes
- Offices
- Car parks
- Covered walkway
- Shopping malls
- Warehouses

Details	Model	RS-PVN-4FT-18W-CW-PC	RS-PV-4FT-18W-CW-PC
Luminous Flux ( Hot Lumens )		1,800lm	2,300lm
Luminous Efficacy		>100 lm/W	>120 lm/W
Colour Temperature		6500k (available 3000k, 4000k)	Warm White (2850K - 3250K)
Beam Angle		180°	300°

