

# LEDVANCE® LED CLASSIC A (170-250V)

LED lamps in classic bulb shapes



## LEDVANCE® LED CLASSIC A (170-250V)

Product Name	GTIN (EAN)	wΔW	E27	W <sup>1</sup>	lm <sup>1</sup>	K	Ra	⌚ <sup>2</sup>	△	d [mm]	t [h] <sup>3</sup>	📦	💡 No.
<b>LEDVANCE® LED CLASSIC A100 (170-250V)</b>													
LV CLA 15W/827 170-250V FR E27	4058075700277	100	E27	15	1,521	2,700	80	–	170°	65	15,000	10	1
LV CLA 15W/865 170-250V FR E27	4058075700307	100	E27	15	1,521	6,500	80	–	170°	65	15,000	10	1
<b>LEDVANCE® LED CLASSIC A75 (170-250V)</b>													
LV CLA 12W/827 170-250V FR E27	4058075700208	75	E27	12	1,055	2,700	80	–	170°	60	15,000	10	1
LV CLA 12W/865 170-250V FR E27	4058075700239	75	E27	12	1,055	6,500	80	–	170°	60	15,000	10	1
<b>LEDVANCE® LED CLASSIC A60 (170-250V)</b>													
LV CLA 9W/827 170-250V FR E27	4058075703360	60	E27	9	806	2,700	80	–	170°	60	15,000	10	1
LV CLA 9W/865 170-250V FR E27	4058075703391	60	E27	9	806	6,500	80	–	170°	60	15,000	10	1
<b>LEDVANCE® LED CLASSIC A50 (170-250V)</b>													
LV CLA 7W/827 170-250V FR E27	4058075700086	50	E27	7	600	2,700	80	–	170°	55	15,000	10	2
LV CLA 7W/865 170-250V FR E27	4058075700116	50	E27	7	600	6,500	80	–	170°	55	15,000	10	2
<b>LEDVANCE® LED CLASSIC A40 (170-250V)</b>													
LV CLA 5W/827 170-250V FR E27	4058075699984	40	E27	5	470	2,700	80	–	170°	55	15,000	10	2
LV CLA 5W/865 170-250V FR E27	4058075700017	40	E27	5	470	6,500	80	–	170°	55	15,000	10	2

<sup>1</sup>Typical values. All the technical parameters apply to the entire lamp. In view of the complex manufacturing process for light emitting diodes, the typical values given above for the technical LED parameters are merely statistical values that do not necessarily correspond to the actual technical parameters of an individual product; individual product may vary from the typical values. For parameter of Lumen and Watt, production control tolerance with ±10% in delivery

<sup>2</sup>The lamp is non-dimmable. Use with dimmer may lead to lamp flicker or product failure

<sup>3</sup>L70B50 is the average operating life of the LED Lamp during which the luminous flux is greater than or equal to 70% of the initial luminous flux, for 50% of the population. The lifetime is estimated at room temperature (25°C), free air burning, base up position

# LEDVANCE® LED CLASSIC A (100-240V)

LED lamps in classic bulb shapes



CRI  
80

## LEDVANCE® LED CLASSIC A (100-240V)

Product Name	GTIN (EAN)	W $\Delta$ W	E27	W <sup>1</sup>	lm <sup>1</sup>	K	Ra	2	3	d [mm]	t [h] <sup>3</sup>	No.	No.
<b>LEDVANCE® LED CLASSIC A100 (100-240V)</b>													
LV CLA 15W/830 100-240V FR E27	4099854020261	40	E27	15	1,521	3,000	80	–	200°	55	25,000	10	1
LV CLA 15W/865 100-240V FR E27	4099854020292	40	E27	15	1,521	6,500	80	–	200°	55	25,000	10	1
<b>LEDVANCE® LED CLASSIC A75 (100-240V)</b>													
LV CLA 12W/830 100-240V FR E27	4099854020209	100	E27	12	1,055	3,000	80	–	180°	60	25,000	10	1
LV CLA 12W/865 100-240V FR E27	4099854020230	100	E27	12	1,055	6,500	80	–	180°	60	25,000	10	1
<b>LEDVANCE® LED CLASSIC A60 (100-240V)</b>													
LV CLA 9W/830 100-240V FR E27	4099854020148	75	E27	9	806	3,000	80	–	180°	60	25,000	10	1
LV CLA 9W/865 100-240V FR E27	4099854020179	75	E27	9	806	6,500	80	–	180°	60	25,000	10	1
<b>LEDVANCE® LED CLASSIC A50 (100-240V)</b>													
LV CLA 7W/830 100-240V FR E27	4099854020087	40	E27	7	600	3,000	80	–	200°	55	25,000	10	2
LV CLA 7W/865 100-240V FR E27	4099854020117	40	E27	7	600	6,500	80	–	200°	55	25,000	10	2
<b>LEDVANCE® LED CLASSIC A40 (100-240V)</b>													
LV CLA 5W/830 100-240V FR E27	4099854020025	40	E27	5	470	3,000	80	–	200°	55	25,000	10	2
LV CLA 5W/865 100-240V FR E27	4099854020056	40	E27	5	470	6,500	80	–	200°	55	25,000	10	2

<sup>1</sup>Typical values. All the technical parameters apply to the entire lamp. In view of the complex manufacturing process for light emitting diodes, the typical values given above for the technical LED parameters are merely statistical values that do not necessarily correspond to the actual technical parameters of an individual product; individual product may vary from the typical values. For parameter of Lumen and Watt, production control tolerance with  $\pm 10\%$  in delivery

<sup>2</sup>The lamp is non-dimmable. Use with dimmer may lead to lamp flicker or product failure

<sup>3</sup>L70B50 is the average operating life of the LED Lamp during which the luminous flux is greater than or equal to 70% of the initial luminous flux, for 50% of the population. The lifetime is estimated at room temperature (25°C), free air burning, base up position