








LED RECESSED DOWNLIGHT

MODEL	 LED-DL-R				 LED-DL-S			
POWER	9W	12W	18W	24W	9W	12W	18W	24W
CCT	3000K (Warm White)			4000K (Cool White)		6000K (Daylight)		
LUMEN	900 - 1100lm	1200 - 1400lm	1800 - 2000lm	2400 - 2600lm	900 - 1100lm	1200 - 1400lm	1800 - 2000lm	2400 - 2600lm
Power Factor	>0.95 PF							
Current Input	220 - 240V 50/60Hz							
SIZE	Ø 149.5mm	Ø 170mm	Ø 223.5mm	Ø 298mm	149.5 x 149.5mm	170 x 170mm	225 x 225mm	294 x 294mm
CUT OUT	Ø 135mm	Ø 155mm	Ø 210mm	Ø 285mm	135 x 135mm	155 x 155mm	210 x 210mm	280 x 280mm
Safety	MS IEC 60598-1 : 2012 , MS IEC 60598-2-2 : 2011 , EN 55015 : 2013 , EN 61547 : 2009 , EN 61000-3-2 : 2014 , EN 62471 : 2008							

 www.facebook.com/imitosbulbs

 www.imitosbulbs.com

 cust-care@imitosbulbs.com



**2 Years
Warranty**

*Terms & Condition Applies