

# LED PERFORMANCE MR16 50 / MR16 35

Low voltage LED reflector lamps MR16



1



## LED PERFORMANCE MR16 50 / MR16 35

Product Name	GTIN (EAN)	w <sub>a</sub> w		W <sup>1</sup>	lm <sup>1</sup>	cd	K	R <sub>a</sub>							
<b>LED PERFORMANCE MR16 50</b>															
LP MR16 50 10 7.5W/927 12V GU5.3	4058075549326	50	GU5.3	7.5	500	3,500	2,700	90	✓	10°	44	50	25,000	10	1
LP MR16 50 10 7.5W/930 12V GU5.3	4058075549340	50	GU5.3	7.5	500	3,500	3,000	90	✓	10°	44	50	25,000	10	1
LP MR16 50 24 7.5W/927 12V GU5.3	4058075535336	50	GU5.3	7.5	700	2,000	2,700	90	✓	24°	44	50	25,000	10	1
LP MR16 50 24 7.5W/930 12V GU5.3	4058075535350	50	GU5.3	7.5	700	2,000	3,000	90	✓	24°	44	50	25,000	10	1
LP MR16 50 36 7.5W/927 12V GU5.3	4058075540187	50	GU5.3	7.5	700	1,000	2,700	90	✓	36°	44	50	25,000	10	1
LP MR16 50 36 7.5W/930 12V GU5.3	4058075540200	50	GU5.3	7.5	700	1,000	3,000	90	✓	36°	44	50	25,000	10	1
LP MR16 50 36 7.5W/965 12V GU5.3	4058075535374	50	GU5.3	7.5	720	1,000	6,500	90	✓	36°	44	50	25,000	10	1
<b>LED PERFORMANCE MR16 35</b>															
LP MR16 35 24 5W/927 12V GU5.3	4058075588431	35	GU5.3	5	380	900	2,700	90	✓	24°	44	50	25,000	10	1
LP MR16 35 36 5W/927 12V GU5.3	4058075588455	35	GU5.3	5	380	700	2,700	90	✓	36°	44	50	25,000	10	1
LP MR16 35 36 5W/930 12V GU5.3	4058075588479	35	GU5.3	5	380	700	3,000	90	✓	36°	44	50	25,000	10	1

<sup>1</sup> Typical values. All the technical parameters apply to the entire lamp. In view of the complex manufacturing process for light emitting diodes, the typical values given above for the technical LED parameters are merely statistical values that do not necessarily correspond to the actual technical parameters of an individual product; individual products may vary from the typical values  
<sup>2</sup> LED lamps can be operated with a wide variety of commercially-available dimmers; details and results of compatibility tests can be seen at [www.ledvance.com/dim](http://www.ledvance.com/dim) and in the additional technical product information sheets linked there  
<sup>3</sup> L70B50 is the average operating life of the LED Lamp during which the luminous flux is greater than or equal to 70% of the initial luminous flux, for 50% of the population. The lifetime is estimated at room temperature (25°C), free air burning, base up burning position and at rated voltage



LEDVANCE is licensee of product trademark OSRAM for lamps products in general lighting.

