

LED PERFORMANCE MR16 50 COB

Dimmable low voltage LED reflector lamps MR16



1



LED PERFORMANCE MR16 50 COB

Product Name	GTIN (EAN)	W ₂ W	W	W ¹	Im ¹	cd	K	Ra	2	3	4	5	6	7	8
LP MR16 50 10D 6W/927 12V COB GU5.3	4099854024832	50	GU5.3	6	580	5,300	2,700	90	✓	10°	44	50	40,000	10	1
LP MR16 50 10D 6W/930 12V COB GU5.3	4099854024856	50	GU5.3	6	580	5,300	3,000	90	✓	10°	44	50	40,000	10	1
LP MR16 50 10D 6W/940 12V COB GU5.3	4099854024870	50	GU5.3	6	580	5,300	4,000	90	✓	10°	44	50	40,000	10	1
LP MR16 50 10D 6W/965 12V COB GU5.3	4099854024894	50	GU5.3	6	580	5,300	6,500	90	✓	10°	44	50	40,000	10	1
LP MR16 50 24D 6W/927 12V COB GU5.3	4099854024597	50	GU5.3	6	580	2,500	2,700	90	✓	24°	44	50	40,000	10	1
LP MR16 50 24D 6W/930 12V COB GU5.3	4099854024610	50	GU5.3	6	580	2,500	3,000	90	✓	24°	44	50	40,000	10	1
LP MR16 50 24D 6W/940 12V COB GU5.3	4099854024634	50	GU5.3	6	580	2,500	4,000	90	✓	24°	44	50	40,000	10	1
LP MR16 50 24D 6W/965 12V COB GU5.3	4099854024658	50	GU5.3	6	580	2,500	6,500	90	✓	24°	44	50	40,000	10	1
LP MR16 50 36D 6W/927 12V COB GU5.3	4099854024672	50	GU5.3	6	580	1,600	2,700	90	✓	36°	44	50	40,000	10	1
LP MR16 50 36D 6W/930 12V COB GU5.3	4099854024696	50	GU5.3	6	580	1,600	3,000	90	✓	36°	44	50	40,000	10	1
LP MR16 50 36D 6W/940 12V COB GU5.3	4099854024719	50	GU5.3	6	580	1,600	4,000	90	✓	36°	44	50	40,000	10	1
LP MR16 50 36D 6W/965 12V COB GU5.3	4099854024733	50	GU5.3	6	580	1,600	6,500	90	✓	36°	44	50	40,000	10	1
LP MR16 50 60D 6W/927 12V COB GU5.3	4099854024757	50	GU5.3	6	580	700	2,700	90	✓	60°	44	50	40,000	10	1
LP MR16 50 60D 6W/930 12V COB GU5.3	4099854024771	50	GU5.3	6	580	700	3,000	90	✓	60°	44	50	40,000	10	1
LP MR16 50 60D 6W/940 12V COB GU5.3	4099854024795	50	GU5.3	6	580	700	4,000	90	✓	60°	44	50	40,000	10	1
LP MR16 50 60D 6W/965 12V COB GU5.3	4099854024818	50	GU5.3	6	580	700	6,500	90	✓	60°	44	50	40,000	10	1

¹ Typical values. All the technical parameters apply to the entire lamp. In view of the complex manufacturing process for light emitting diodes, the typical values given above for the technical LED parameters are merely statistical values that do not necessarily correspond to the actual technical parameters of an individual product; individual products may vary from the typical values

² L70B50 is the average operating life of the LED Lamp during which the luminous flux is greater than or equal to 70% of the initial luminous flux, for 50% of the population. The lifetime is estimated at room temperature (25°C), free air burning, base up burning position and at rated voltage

³ The Tc is defined as the highest permissible temperature which may occur on the outer surface of the LED lamp (in the indicated position) under normal operating conditions and at the rated voltage/current/power or the maximum of the rated voltage/current/power range (DIN EN 62031: 2009-01)