

LED VALUE PAR16 80 / PAR16 50

LED reflector lamps PAR16



LED VALUE PAR16 80 / PAR16 50

Product Name	GTIN (EAN)	wΔW	mm	W ¹	lm ¹	cd	K	Ra	° ²	△°	l [mm]	d [mm]	t [h] ³	No.	
LED VALUE PAR16 80															
LV PAR16 80 36 7W/827 230V GU10	4058075587755	80	GU10	7	630	850	2,700	80	–	36°	52	50	15,000	10	1
LV PAR16 80 36 7W/840 230V GU10	4058075587793	80	GU10	7	650	1,000	4,000	80	–	36°	52	50	15,000	10	1
LV PAR16 80 36 7W/865 230V GU10	4058075587830	80	GU10	7	650	1,000	6,500	80	–	36°	52	50	15,000	10	1
LED VALUE PAR16 50															
LV PAR16 50 24 4.5W/827 230V GU10	4058075588417	50	GU10	4.5	380	1,000	2,700	80	–	24°	54	50	15,000	10	2
LV PAR16 50 36 4.5W/827 230V GU10	4058075588356	50	GU10	4.5	380	750	2,700	80	–	36°	54	50	15,000	10	2
LV PAR16 50 36 4.5W/840 230V GU10	4058075588370	50	GU10	4.5	400	750	4,000	80	–	36°	54	50	15,000	10	2
LV PAR16 50 36 4.5W/865 230V GU10	4058075588394	50	GU10	4.5	420	800	6,500	80	–	36°	54	50	15,000	10	2

¹ Typical values. All the technical parameters apply to the entire lamp. In view of the complex manufacturing process for light emitting diodes, the typical values given above for the technical LED parameters are merely statistical values that do not necessarily correspond to the actual technical parameters of an individual product; individual products may vary from the typical values

² LED lamps can be operated with a wide variety of commercially-available dimmers; details and results of compatibility tests can be seen at www.ledvance.com/dim and in the additional technical product information sheets linked there

³ L70B50 is the average operating life of the LED Lamp during which the luminous flux is greater than or equal to 70% of the initial luminous flux, for 50% of the population. The lifetime is estimated at room temperature (25°C), free air burning, base up burning position and at rated voltage



LEDVANCE is licensee of product trademark OSRAM for lamps products in general lighting.

