

# SubstiTUBE® ADVANCED AC T5 HE & HO

LED replacement for traditional fluorescent T5 tube with long lifetime



1

GLASS

CRI  
>80

## SubstiTUBE® ADVANCED AC T5 HE & HO

Product Name	GTIN (EAN)	$w_{\Delta W}$	$\Sigma$	W <sup>1</sup>	lm <sup>1</sup>	K	Ra	$\varnothing$ <sup>2</sup>	$\Delta$	$\frac{l}{d}$ <sup>3</sup>	t(h)		No.
<b>SubstiTUBE® ADVANCED AC T5 HE</b>													
ST5 HE 35 1.5M 18W/840 230V AC	4058075543485	1,463.2mm	G5	18	2,800	4,000	>80	—	>160°	1,463.2	50,000	10	1
ST5 HE 35 1.5M 18W/865 230V AC	4058075543508	1,463.2mm	G5	18	2,800	6,500	>80	—	>160°	1,463.2	50,000	10	1
ST5 HE 28 1.2M 16W/830 230V AC	4058075556379	1,163.2mm	G5	16	2,160	3,000	>80	—	>160°	1,163.2	50,000	10	1
ST5 HE 28 1.2M 16W/840 230V AC	4058075543522	1,163.2mm	G5	16	2,400	4,000	>80	—	>160°	1,163.2	50,000	10	1
ST5 HE 28 1.2M 16W/865 230V AC	4058075543546	1,163.2mm	G5	16	2,400	6,500	>80	—	>160°	1,163.2	50,000	10	1
ST5 HE 14 0.6M 8W/830 230V AC	4058075556232	563.2mm	G5	8	1,080	3,000	>80	—	>160°	563.2	50,000	10	1
ST5 HE 14 0.6M 8W/840 230V AC	4058075543560	563.2mm	G5	8	1,200	4,000	>80	—	>160°	563.2	50,000	10	1
ST5 HE 14 0.6M 8W/865 230V AC	4058075543584	563.2mm	G5	8	1,200	6,500	>80	—	>160°	563.2	50,000	10	1
<b>SubstiTUBE® ADVANCED AC T5 HO</b>													
ST5 HO 80 1.5M 37W/840 230V AC	4058075543362	1,463.2mm	G5	37	5,600	4,000	>80	—	>160°	1,463.2	50,000	10	1
ST5 HO 80 1.5M 37W/865 230V AC	4058075543386	1,463.2mm	G5	37	5,600	6,500	>80	—	>160°	1,463.2	50,000	10	1
ST5 HO 49 1.5M 26W/840 230V AC	4058075543447	1,463.2mm	G5	26	4,000	4,000	>80	—	>160°	1,463.2	50,000	10	1
ST5 HO 49 1.5M 26W/865 230V AC	4058075543461	1,463.2mm	G5	26	4,000	6,500	>80	—	>160°	1,463.2	50,000	10	1
ST5 HO 54 1.2M 26W/840 230V AC	4058075543409	1,163.2mm	G5	26	4,000	4,000	>80	—	>160°	1,163.2	50,000	10	1
ST5 HO 54 1.2M 26W/865 230V AC	4058075543423	1,163.2mm	G5	26	4,000	6,500	>80	—	>160°	1,163.2	50,000	10	1

<sup>1</sup> All technical parameters apply to the complete lamp. Due to the complex manufacturing process of light emitting diodes, the specified typical values of the LED parameters merely represent purely statistical variables. They do not necessarily correspond to the actual technical parameters or each individual product, which can deviate from the typical value

<sup>2</sup> LED lamps can be operated with a wide variety of commercially-available dimmers; details and results of compatibility tests can be seen at [www.ledvance.com/dim](http://www.ledvance.com/dim) and in the additional technical product information sheets linked there

<sup>3</sup> L70/B50