

SubstiTUBE® ECO AC T5 HE & HO

LED replacement for traditional fluorescent T5 tube with long lifetime



1



SubstiTUBE® ECO AC T5 HE & HO

Product Name	GTIN (EAN)	$w_{\Delta W}$	Σ	W ¹	lm ¹	K	R _a	ω ²	θ	L [mm]	t [h] ³		
SubstiTUBE® ECO AC T5 HE													
ST5 35E 1.5M 18W/840 230V AC HE	4058075757288	1,463.2mm	G5	18	2,000	4,000	>80	–	>160°	1,463.2	20,000	25	1
ST5 35E 1.5M 18W/865 230V AC HE	4058075757301	1,463.2mm	G5	18	2,000	6,500	>80	–	>160°	1,463.2	20,000	25	1
ST5 28E 1.2M 16W/840 230V AC HE	4058075757240	1,163.2mm	G5	16	1,800	4,000	>80	–	>160°	1,163.2	20,000	25	1
ST5 28E 1.2M 16W/865 230V AC HE	4058075757264	1,163.2mm	G5	16	1,800	6,500	>80	–	>160°	1,163.2	20,000	25	1
ST5 14E 0.6M 8W/840 230V AC HE	4058075757202	563.2mm	G5	8	900	4,000	>80	–	>160°	563.2	20,000	25	1
ST5 14E 0.6M 8W/865 230V AC HE	4058075757226	563.2mm	G5	8	900	6,500	>80	–	>160°	563.2	20,000	25	1
SubstiTUBE® ECO AC T5 HO													
ST5 80E 1.5M 37W/840 230V AC HO	4058075757363	1,463.2mm	G5	37	4,800	4,000	>80	–	>160°	1,463.2	20,000	25	1
ST5 80E 1.5M 37W/865 230V AC HO	4058075757387	1,463.2mm	G5	37	4,800	6,500	>80	–	>160°	1,463.2	20,000	25	1
ST5 54E 1.2M 26W/840 230V AC HO	4058075757325	1,163.2mm	G5	26	2,860	4,000	>80	–	>160°	1,163.2	20,000	25	1
ST5 54E 1.2M 26W/865 230V AC HO	4058075757349	1,163.2mm	G5	26	2,860	6,500	>80	–	>160°	1,163.2	20,000	25	1

¹ All technical parameters apply to the complete lamp. Due to the complex manufacturing process of light emitting diodes, the specified typical values of the LED parameters merely represent purely statistical variables. They do not necessarily correspond to the actual technical parameters or each individual product, which can deviate from the typical value

² LED lamps can be operated with a wide variety of commercially-available dimmers; details and results of compatibility tests can be seen at www.ledvance.com/dim and in the additional technical product information sheets linked there

³ L70/B50