

SubstiTUBE® VALUE AC T5 HE

LED replacement for traditional fluorescent T5 tube with G5 base



1



SubstiTUBE® VALUE AC T5 HE

Product Name	GTIN (EAN)	$w_{\Delta W}$	Σ	W ¹	lm ¹	K	R _a	ω ²	Δ	$\frac{l}{[mm]}$	t(h) ³		
ST5 HE V 1.2M 15W/840 230V AC	4058075556430	1,163.2mm	G5	15	1,800	4,000	>80	–	>160°	1,163.2	30,000	10	1
ST5 HE V 1.2M 15W/865 230V AC	4058075556454	1,163.2mm	G5	15	1,800	6,500	>80	–	>160°	1,163.2	30,000	10	1
ST5 HE V 0.6M 8W/840 230V AC	4058075556393	563.2mm	G5	8	960	4,000	>80	–	>160°	563.2	30,000	10	1
ST5 HE V 0.6M 8W/865 230V AC	4058075556416	563.2mm	G5	8	960	6,500	>80	–	>160°	563.2	30,000	10	1

¹ All technical parameters apply to the complete lamp. Due to the complex manufacturing process of light emitting diodes, the specified typical values of the LED parameters merely represent purely statistical variables. They do not necessarily correspond to the actual technical parameters of each individual product, which can deviate from the typical value

² LED lamps can be operated with a wide variety of commercially-available dimmers; details and results of compatibility tests can be seen at www.ledvance.com/dim and in the additional technical product information sheets linked there

³ L70/B50