LED PIN 12V

Low-voltage 12V LED lamps with retrofit pin base







LED PIN 12V

Product Name	GTIN (EAN)	w≙W	N.	W	(Im)	K	Ra	o contraction of the contraction		[mm]	Ø (mm)	t [h]		No.
LED PIN 40 DIM 4.5W/827 12V GY6.35	4058075607255	40	GY6.35	4.5	470	2,700	80	1	300°	50	18	25,000	6	1
LED PIN 40 4W/827 12V GY6.35	4058075607224	40	GY6.35	4	470	2,700	80	_	300°	50	18	15,000	6	2
LED PIN 30 2.6W/827 12V GY6.35	4058075432123	30	GY6.35	2.6	300	2,700	80	_	300°	40	14	15,000	6	3
LED PIN 30 2.6W/827 12V G4	4058075431997	30	G4	2.6	300	2,700	80	_	300°	40	14	15,000	6	4
LED PIN 20 DIM 2W/827 12V G4	4058075431904	20	G4	2	200	2,700	80	1	300°	40	15	25,000	6	5
LED PIN 20 1.8W/827 12V G4	4058075431966	20	G4	1.8	200	2,700	80	_	300°	36	13	15,000	6	6
LED PIN 10 0.9W/827 12V G4	4058075431935	10	G4	0.9	100	2,700	80	_	300°	33	12	15,000	6	7



Applicable for LED PIN 40 DIM 4.5W/827 12V GY6.35 & LED PIN 20 DIM 2W/827 12V G4

¹ All technical parameters apply to the complete lamp. Due to the complex manufacturing process of light emitting diodes, the specified typical values of the LED parameters merely represent purely statistical variables. They do not necessarily correspond to the actual technical parameters or each individual product, which can deviate from the typical value

² LED lamps can be operated with a wide variety of commercially-available dimmers; details and results of compatibility tests can be seen at www.ledvance.com/dim and in the additional technical product information sheets linked there

³ L70/B50