




LED PIN G9

LED lamps with retrofit pin base G9



LED PIN G9

Product Name	GTIN (EAN)	$w \pm W$	\varnothing	W ¹	lm ¹	K	R _a	 ²	Δ ²	$\frac{l}{d}$ [mm]	\varnothing d [mm]	t [h] ³		
LED PIN 50 4.8W/827 230V G9	4058075432451	50	G9	4.8	600	2,700	80	–	300°	59	18	15,000	6	1
LED PIN 40 DIM 4W/827 230V G9	4058075432246	40	G9	4	470	2,700	80	✓	300°	59	18	25,000	6	2
LED PIN 40 4.2W/827 230V CL G9	4058075432390	40	G9	4.2	470	2,700	80	–	300°	52	20	15,000	6	3
LED PIN 30 DIM 3W/827 230V G9	4058075607286	30	G9	3	320	2,700	80	✓	300°	52	16	25,000	6	4
LED PIN 30 2.6W/827 230V CL G9	4058075432338	30	G9	2.6	320	2,700	80	–	300°	47	15	15,000	6	5
LED PIN 20 1.9W/827 230V CL G9	4058075432307	20	G9	1.9	200	2,700	80	–	300°	46	15	15,000	6	6

¹ All technical parameters apply to the complete lamp. Due to the complex manufacturing process of light emitting diodes, the specified typical values of the LED parameters merely represent purely statistical variables. They do not necessarily correspond to the actual technical parameters or each individual product, which can deviate from the typical value

² LED lamps can be operated with a wide variety of commercially-available dimmers; details and results of compatibility tests can be seen at www.ledvance.com/dim and in the additional technical product information sheets linked there

³ L70/B50