

LED PERFORMANCE DIMMABLE FILAMENT CLASSIC A/B LED VALUE FILAMENT CLASSIC A

LED lamps with filament-style LED technology and TruWave Technology™



LED PERFORMANCE DIMMABLE FILAMENT CLASSIC A/B

Product Name	GTIN (EAN)	W _{LED}	W	Im ¹	K	Ra	2	3	d (mm)	t (h) ³	No.		
LED PERFORMANCE DIMMABLE FILAMENT CLASSIC A													
LP CLA DIM 7.5W/827 230V FIL E27	4058075751361	75	E27	7.5	1,055	2,700	80	✓	300°	60	15,000	10	1
LP CLA DIM 7.5W/840 230V FIL E27	4058075751415	75	E27	7.5	1,055	4,000	80	✓	300°	60	15,000	10	1
LP CLA DIM 7.5W/827 230V GL FR E27	4058075751453	75	E27	7.5	1,055	2,700	80	✓	300°	60	15,000	10	2
LP CLA DIM 7.5W/840 230V GL FR E27	4058075751491	75	E27	7.5	1,055	4,000	80	✓	300°	60	15,000	10	2
LED PERFORMANCE DIMMABLE FILAMENT CLASSIC B													
LP CLB DIM 4W/827 230V GL FR E14	4058075751590	40	E14	4	470	2,700	80	✓	300°	35	15,000	10	3
LP CLB DIM 4W/840 230V GL FR E14	4058075751613	40	E14	4	470	4,000	80	✓	300°	35	15,000	10	3

LED VALUE FILAMENT CLASSIC A

Product Name	GTIN (EAN)	W _{LED}	W	Im ¹	K	Ra	2	3	d (mm)	t (h) ³	No.		
LV CLA 4W/827 230V FIL E27	4058075267169	40	E27	4	470	2,700	80	–	300°	60	15,000	10	1
LV CLA 4W/840 230V FIL E27	4058075267206	40	E27	4	470	4,000	80	–	300°	60	15,000	10	1
LV CLA 7W/827 230V FIL E27	4058075267220	60	E27	7	806	2,700	80	–	300°	60	15,000	10	1
LV CLA 7W/840 230V FIL E27	4058075751538	60	E27	7	806	4,000	80	–	300°	60	15,000	10	1
LV CLA 7W/827 230V GL FR E27	4058075751552	60	E27	7	806	2,700	80	–	300°	60	15,000	10	2
LV CLA 7.5W/827 230V FIL E27	4058075506655	75	E27	7.5	1,055	2,700	80	–	300°	60	15,000	10	1
LV CLA 7.5W/840 230V FIL E27	4058075506652	75	E27	7.5	1,055	4,000	80	–	300°	60	15,000	10	1

¹ Typical values. All the technical parameters apply to the entire lamp. In view of the complex manufacturing process for light emitting diodes, the typical values given above for the technical LED parameters are merely statistical values that do not necessarily correspond to the actual technical parameters of an individual product; individual product may vary from the typical values. For parameter of Lumen and Watt, production control tolerance with ±10% in delivery

² The lamp is non-dimmable. Use with dimmer may lead to lamp flicker or product failure

³ L70B50 is the average operating life of the LED Lamp during which the luminous flux is greater than or equal to 70% of the initial luminous flux, for 50% of the population. The lifetime is estimated at room temperature (25°C), free air burning, base up position



LEDVANCE is licensee of product trademark OSRAM for lamps products in general lighting.

