

MIWIO

UPGRADE YOUR LIGHTSTYLE
BY ELEGANT

SUPER BRIGHT

LED FLOOD LIGHT

features

- ⇒ Designed for outdoor use
- ⇒ Designed for a connection with a AC 100 ~ 240 V / 50 ~ 60 Hz
- ⇒ Major power saving, high efficiency with low cost of consumptions
- ⇒ Well performance at 25°C
- ⇒ Power factor: 0.5



standard specification

Long Lifetime

20,000 hours



Colour Temp

available in
daylight (6500K)

Applications



Approved by:



Watt (W)	Length (mm) [A]	Height (mm) [B]	Width (mm) [C]
10	103	94	23
20	121	108	21
30	170	143	31
50	235	180	30
100	305	240	36
150	370	280	83
200	440	335	95

Description	Watt (W)	Voltage (V)	Lumen (LM)	CCT	CRI	Standard Pack
MW-10FL	10	AC 100 ~ 240 V	1000	6500 K	≥ 80	50 pcs/ ctn
MW-20FL	20	AC 100 ~ 240 V	2000	6500 K	≥ 80	50 pcs/ ctn
MW-30FL	30	AC 100 ~ 240 V	3000	6500 K	≥ 80	20 pcs/ ctn
MW-50FL	50	AC 100 ~ 240 V	5000	6500 K	≥ 80	20 pcs/ ctn
MW-100FL	100	AC 100 ~ 240 V	10000	6500 K	≥ 80	10 pcs/ ctn
MW-150FL	150	AC 100 ~ 240 V	15000	6500 K	≥ 80	4 pcs/ ctn
MW-200FL	200	AC 100 ~ 240 V	20000	6500 K	≥ 80	4pcs/ ctn