

# LED T8 GLASS TUBE PF 0.95

## features

- ⇒ Up to 50% energy saving compared to fluorescent lamps
- ⇒ Bright and uniform light output
- ⇒ Short start-up time, and easy to install
- $\Rightarrow$  100% light when switched on, no run up time
- ⇒ High colour rendering index, restore true colour of environment
- ⇒ Environment friendly and safe, with no pollution, in accordance with ROHS standards
- $\Rightarrow$  Adopt constant current driver switching power supply, input voltage 170  $\sim$  265 V
- ⇒ Power Factor: 0.95

# standard specification

#### **Long Lifetime**

30,000 hours

### **Colour Temp**

available in

warmwhite (3000K)

coolwhite (4000K)

daylight (6500K)

# **Applications**








### **Environmental Conscious**

no UV, IR and mercury pollution in line with the relevant recognition permit requirements







#### Approved by:







Watt (W)	Length (mm)	Width (mm)
10	600	28
22	1200	28

Description	Watt (W)	Voltage (V)	Lumen (LM)	ССТ	Beam Angle	Standard Pack
CSG-T8102	10	AC 170 ~ 265	1000	3000K, 4000K, 6500K	270°	25 pcs/ ctn
CSG-T8184	22	AC 170 ~ 265	2000	3000K, 4000K, 6500K	270°	25 pcs/ ctn