

BELEGANT

BRIGHT MAKER



LED RIMLESS SURFACE LIGHT

features

- ⇒ Built-in with internal isolation driver for better performance
- ⇒ Elegant appearance, to brighten up your space
- ⇒ Major power savings, up to 90% power efficiency
- ⇒ Made out of die cast aluminum
- ⇒ No dark spot, soft and uniform light, comfortable to eyes
- ⇒ Low light decay
- ⇒ High colour rendering index, restore true colour of environment
- ⇒ Designed for a connection with AC 85V ~ 265V



standard specification

Lifetime

25,000 hours

Colour Temp

available in

warmwhite (3000K)

coolwhite (4000K)

daylight (6500K)

Applications




Shape

available in

round (R)

square (S)



Size (inch)	Height (mm)	Length (mm)
6	170	170
8	220	220
12	300	300

Description	Watt (W)	Lumen (LM)	Size	CCT	Shape	CRI	Standard Pack
BELG-SRL20S	20	1800	6 inch	3000K, 4000K, 6500K	Square	≥ 80	40 pcs/ ctn
BELG-SRL20R	20	1800	6 inch	3000K, 4000K, 6500K	Round	≥ 80	40 pcs/ ctn
BELG-SRL26S	26	2340	8 inch	3000K, 4000K, 6500K	Square	≥ 80	30 pcs/ ctn
BELG-SRL26R	26	2340	8 inch	3000K, 4000K, 6500K	Round	≥ 80	30 pcs/ ctn
BELG-SRL38S	38	3420	12 inch	3000K, 4000K, 6500K	Square	≥ 80	10 pcs/ ctn
BELG-SRL38R	38	3420	12 inch	3000K, 4000K, 6500K	Round	≥ 80	10 pcs/ ctn